



LUBLAN SEO 4T 20W40

Lubricant for 4-stroke motorcycles

Product Description:

SEO 4T 20W-40 is a high performance conventional four-stroke motorcycle engine oil primarily intended for general use in all types of four-stroke motorcycles and engines.

Features and Benefits:

- Maximum protection and engine cleanliness. Optimizes performance of the clutch and gearshift. It facilitates cold starts
- Suitable for all types of 4 stroke bikes up to 150 cc
- Excellent operation at high temperature condition
- Reduced environmental impact thanks to lower fuel consumption and reduced emissions.
- High detergent and dispersant properties keep the engine, gear and wet clutch clean.

Specifications and Approval:

Exceeds requirements: **API SL, JASO MA2**

Typical properties:

LUBLAN SEO 4T 20W40

SAE Grade	20W40
Viscosity ASTM D-445	
cSt @ 100°C	14,6 – 15,2
Viscosity Index ASTM D-2270	≥130
Pour Point, °C, ASTM D-97	≤-30
Flash Point, °C, ASTM D-92	≥230
Density @ 15°C, Kg/l, ASTM D-1298	≥0,880

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

SEO 4T 20W40 Date Created: 18/01/2013 Last Edit: 20/07/2018

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofongone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it

P. IVA e C.F. 02682090648