



CHALLOILS®

CHALLOILS CATALIST 15W-40

Passenger Cars Motor Oil

Product Description:

CATALIST 15W-40 it employs selected mineral bases, additives and modern high-performance technology. This allows to obtain a very high level of protection in spite of the 'engine wear, a good fluidity at low temperatures, a control of the volatility and the viscosity retention at high temperatures. It recommended use in all weather conditions.

Features and Benefits:

- Excellent protection throughout the oil change interval period.
- Fast lubrication.
- Good fluidity at low temperatures.

Specifications and Approval:

Exceeds requirements: **API SM/CF; FIAT 9.55535-G2**

Typical properties:

CHALLOILS CATALIST 15W-40

SAE Grade	15W-40
Viscosity ASTM D-445	
cSt @ 40°C	96 – 106
cSt @ 100°C	13,5 – 14,6
Viscosity Index ASTM D-2270	≥120
Pour Point, °C, ASTM D-97	≤-27
Flash Point, °C, ASTM D-92	>220
Density @ 15°C, Kg/l, ASTM D-1298	≥0,860

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

CATALIST 15W-40 Date Created: 18/01/2013 Last Edit: 20/07/2018

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofangone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it

P. IVA e C.F. 02682090648