



# CHALLOILS®

## **CHALLOILS DYNAMICSTROKE 2T**

*Lubricant for 2-stroke engines*

### **Product Description:**

Lubricant for 2-stroke engines with mixture or separate lubrication, equipped with air or water cooling. Recommended for mopeds, scooters, motorcycles, vans, and work equipment.

### **Features and Benefits:**

- High protection and engine cleanliness.
- Anti seizing and wear properties.
- Smokiness contained.
- Properties detergents that prevent piston ring sticking and clogging of the exhaust ports.
- Can be used with unleaded petrol.

### **Specifications and Approval:**

Exceeds requirements: **API TC, JASO FB**

### **Typical properties:**

### **CHALLOILS DYNAMICSTROKE 2T**

Viscosity ASTM D-445

cSt @ 40°C	62 – 70
------------	---------

cSt @ 100°C	8,8 – 9,4
-------------	-----------

Viscosity Index ASTM D-2270	≥110
-----------------------------	------

Pour Point, °C, ASTM D-97	≤-12
---------------------------	------

Flash Point, °C, ASTM D-92	≥100
----------------------------	------

Density @ 15°C, Kg/l, ASTM D-1298	≥0,860
-----------------------------------	--------

### **Health and Safety:**

The data related to health, safety and environmental protection are provided in the material safety data sheets.

*The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.*

**DYNAMICSTROKE 2T** Date Created: 18/01/2013 Last Edit: 20/07/2018

*This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.*

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofangone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: [info@gloil.it](mailto:info@gloil.it)

P. IVA e C.F. 02682090648