



CHALLOILS LITHIUM GREASE NLGI 00

Fats of general use

Product Description:

LITHIUM GREASE NLGI 00 is a high-performance lithium grease, formulated for high protection against wear, rust and water washout.

Application:

This fat is particularly suitable for the lubrication of gears and bearings in poorly sealed gear cases recommended for many industrial applications. Main impiego on machinery of any type in which a grease lubrication is required in the presence of high loads, (EP) impact or vibration (earth moving machines, machine tools and textiles, pumps, electric motors, etc.). They can also be used for the lubrication of pins, joints, articulated joints, rails, racks, etc. The operating temperatures may vary from -25 ° C to + 130 ° C.

Features and Benefits:

- Universality of use
- A long operating life.
- Excellent mechanical stability.
- Excellent lubricating properties.
- Good rust protection.
- Good water resistance.

Typical properties:

LITHIUM GREASE NLGI 00

Thickener	Lithium
Consistency NLGI	00
Appearance	Smooth-textured
Color	Amber
Poit Drop, °C, ASTM D-556	>185
Worked Penetration, 60 colpi a 25°C, dmm, ISO 2137	400
Corrosion Test, ASTM D-1743	Pass
Oxidation stability (100 h at 100°C), Kg/cm ² , ASTM D-942	<0,5
Washout resistance (1 h at 79°C), %, ASTM D-1264	5
Classification DIN, DIN-51502	K1K-30

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

LITHIUM GREASE NLGI 00 Date Created: 18/01/2013 Last modification: 20/07/2018

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofongone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it

P. IVA e C.F. 02682090648