



CHALLOILS®

CHALLOILS PROGRESS 20W50

Lubricant for petrol and diesel engines

Product Description:

PROGRESS 20W-50 is a mineral oil formulated with additives of modern high-performance technology. This allows to obtain a very high level of protection in spite of the engine wear, a good fluidity at low temperatures, a control of the volatility and the viscosity retention at high temperatures. It recommended use in all weather conditions.

Features and Benefits:

- Excellent protection during the whole period of the oil change interval.
- Rapid lubrication.
- Good low temperature fluidity.

Specifications and Approval:

Exceeds requirements: API SN/CF, ACEA A3/B3, MB 228.1, VW 501.01/505.00

Typical properties:

CHALLOILS PROGRESS 20W50

SAE Grade	20W-50
Viscosity ASTM D-445 cSt @ 100°C	16,5 – 17,7
Viscosity Index ASTM D-2270	≥125
Pour Point, °C, ASTM D-97	≤-25
Flash Point, °C, ASTM D-92	220
Density @ 15°C, Kg/l, ASTM D-1298	≥0,870

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

PROGRESS 20W-50 Date Created: 18/01/2013 Last Edit: 20/07/2018

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.