



CHALLOILS ULTRASYNT 5W-40

Fully synthetic engine oil

Product Description:

ULTRASYNT 5W-40 is a 100% synthetic lubricant of the latest generation, developed to meet the requirements of a large number of cars of the world's leading manufacturers. And 'suitable for gasoline engines, both aspirated and turbo, and diesel and turbodiesel engines. And 'particularly suitable for modern turbodiesel direct injection.

Features:

ULTRASYNT 5W-40 makes use of sophisticated formulation and top-quality components technologies to enable the achievement of extended oil drain intervals set by a large number of manufacturers with maximum safety and economy.

ensures:

- Maximum durability of the engine.
- Higher efficiency in energy terms.
- Silent operation.
- Reduction of harmful emissions.

Specifications and Approval:

Exceeds requirements: **ACEA C3, API SN/CF, VW 502.00/505.00/505.01, MB- 229.51, BMW Longlife-04, Ford WSS-M2C917-A, Porsche A40, Renault RN 0700/0710; FIAT 9.55535-S1/S2**

Typical properties:

CHALLOILS ULTRASYNT 5W-40

SAE Grade	5W-40
Viscosity ASTM D-445	
cSt @ 40°C	79 – 88
cSt @ 100°C	13,4 – 14,8
Viscosity Index, ASTM D-2270	≥150
Pour Point, °C, ASTM D-97	≤-30
Flash Point, °C, ASTM D-92	≥210
Density @ 15°C, Kg/l, ASTM D-1298	≥0,855

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

ULTRASYNT 5W-40 Date Created: 18/01/2013 Last Edit: 20/07/2018

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofongone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it

P. IVA e C.F. 02682090648