



LUBLAN ABF DOT 5.1

Fluid for braking systems

Product Description:

ABF DOT 5.1 is a high boiling point non-silicone fluid for disc brakes and a drum, meeting the specifications SAE J 1703 / J 1704, FMVSS 116, DOT 5.1, CUNA NC 956 DOT 5.1. ISO 4925 Class 5.1

Features and Benefits:

- High boiling point: it can be used without forming within the fluid, dangerous vapor bubbles.
- Low viscosity at -40 ° C
- Anti-corrosive properties towards all metals
- Good chemical stability

Specifications and Approval:

Exceeds requirements: **FMVSS 116 DOT 5.1, SAE J 1703/J 1704, CUNA NC 956 DOT 5.1, ISO 4925 Class 5.1**

Typical properties:

LUBLAN ABF DOT 5.1

Boiling Point, °C	175
Boiling Point (RPB), °C	275
Viscosity, cSt @ 40°C	850
Viscosity, cSt @ 100°C	2.0
Density @ 20°C, Kg/l, ASTM D-1298	1075
pH	9,0

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.
ABF DOT 5.1 Date Created: 18/01/2013 Last Ed 17/05/2019

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofangone Zona ASI Nola-Marigliano - 80035 Nola (Na)
Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it
P. IVA e C.F. 02682090648



This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.