



**LUBLAN ACF RTU 40**  
*Protective fluid for cooling systems*

**Product Description:**

Liquid "ready to use" based on mono ethylene glycol and an additive system unconventional free from nitrites, amines and phosphates. Formulated for use directly, without further addition of water, in cooling circuits of any engine (gasoline or diesel) mounted on cars, commercial vehicles, agricultural and construction equipment.

It also suitable for static or marine engines and for water-cooled motorcycle engines. Ensure effective protection and can remain in service for at least 2 years or 60,000 km.

**Features and Benefits:**

- Protection against freezing: -26 ° C
- Very high resistance to fizzed.
- It prevents the formation of deposits and encrustations.
- High boiling point.
- Prevention of erosion by cavitation.
- Maximum protection of all components.

**Specifications and Approval:**

Exceeds requirements: **AFNOR 15-601 Type 2, BS 6580, CUNA NC956-16, SAE J 1034**

**Typical properties:**

**LUBLAN ACF RTU 40**

Appearance	Clear
Color	Blue
Boiling Point, °C, ASTM D-1120	105
Pour Point, °C, ASTM D-1177	-26
Density @ 15°C, Kg/l, ASTM D-1298	1060
pH (sol. At 50%), ASTM D-1287	7,2

**Health and Safety:**

The data related to health, safety and environmental protection are provided in the material safety data sheets.

*The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.*

ACF RTU 40 Date Created: 18/01/2013 Last Edit: 17/05/2019

*This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.*

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofangone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: [info@gloil.it](mailto:info@gloil.it)

P. IVA e C.F. 02682090648