



LUBLAN AGO 75W-80
Lubricant for manual transmissions

Product Description:

AGO 75W-80 it is a high performance lubricant for manual transmissions, used on commercial vehicles and motor vehicles. This lubricant is developed using advanced technology base oils and additives provides better fluidity at low temperatures and higher viscosity at high temperatures
Recommended for all types of manual transmissions of cars, commercial vehicles and construction equipment requiring an SAE 75W-80 grade lubricant with EP (API GL-3/4).

Features and Benefits:

- Reduction of noise, heat, transmissions and in particular of the synchronizer.
- Excellent protection against the formation of deposits and varnish.
- Effective protection against gear wear and corrosion.
- Reduced internal friction and fuel consumption (fuel economy).
- Excellent low temperature fluidity.
- Excellent thermal stability and oxidation that enable a significantly increased service life.

Specifications and Approval:

Exceeds requirements: **API GL-4, MAN 341 Tipo E3, ZF TE-ML 02D**

Typical properties:

LUBLAN AGO 75W80

SAE Grade	75W80
Viscosity ASTM D-445	
cSt @ 40°C	48 – 54
cSt @ 100°C	8,7 – 9,6
Viscosity Index ASTM D-2270	≥160
Pour Point, °C, ASTM D-97	-44
Flash Point, °C, ASTM D-92	≥220
Density @ 15°C, Kg/l, ASTM D-1298	≥0,870

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

AGO 75W-80 Date Created: 18/01/2013 Last Edit: 17/05/2019

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofongone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it

P. IVA e C.F. 02682090648