



LUBLAN ATF 8-SPEED

Synthetic Fluid ATF type for transmissions

Product Description:

ATF 8-SPEED is a fully synthetic with a special additivation and inhibition which guarantees a perfect function of the automatic transmission.

ATF 8-SPEED is a automatic transmission oil ATF of the latest generation for all 8 stroke automatic transmissions of ZF. It guarantee in any mode for maximum wear protection.

Features and Benefits:

Very good lubricating ability even at low temperatures in winter

- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- A high thermal and oxidative stability
- An excellent cooling capacity

Specifications and Approval:

Exceeds requirements: **BMW 83222289720, VW G 055 162, ZF S671 090 312, Fiat 9.55550-AV5, Land Rover LR023288**

Typical properties:

LUBLAN ATF 8-SPEED

Viscosity ASTM D-445	
cSt @ 40°C	27,2 – 29,8
cSt @ 100°C	5,6 – 5,9
Viscosity Index ASTM D-2270	≥150
Pour Point, °C, ASTM D-97	-45
Flash Point, °C, ASTM D-92	>210
Density @ 15°C, Kg/l, ASTM D-1298	≥0,850
Color	Green

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

ATF 8-SPEED Date Created: 18/01/2013 Last Edit: 17/05/2019

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofangone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it

P. IVA e C.F. 02682090648