



LUBLAN DIELETRIC OIL

Product Description:

The Dielectric Oil is a dielectric fluid for transformers, switches and rheostats. It has a high resistance to chemical and thermal degradation and reduces the formation of sludge and oxidation products. The low pour point ensures ready movement even at low temperatures, while the low viscosity enables rapid heat transfer for convection.

Features:

- High insulation
- Excellent resistance to chemical and thermal degradation
- Good resistance to the formation of sludge
- Low pour point for a good fluidity at all temperatures

Typical properties: *LUBLAN DIELETRIC OIL*

Viscosity ASTM D-445

cSt @ 40°C	15
Pour Point, °C, ASTM D-97	-35
Flash Point, °C, ASTM D-92	>150
Density @ 15°C, Kg/l, ASTM D-1298	≥0,860

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

DIELETRIC OIL Date Created: 18/01/2013 Last Edit: 20/07/2018

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.