



LUBLAN LS 250

Anti-wear lubricant for mechanical transmissions

Product Description:

Gradation lubricant SAE 250, specially formulated for the lubrication of manual transmissions in which they are not required lubricant with EP characteristics and changes with a synchronizer. In particular it is suitable for gearboxes and gearbox / differential groups (in the absence of torque hypoid).

Features and Benefits:

- Adjust the synchronizer service even in severe service.
- Marked anti-wear characteristics that ensure long life of bearings, gears, shafts and synchronizers.
- Excellent thermal stability and minimum change in viscosity (thickening).
- Perfect cleaning of the various gearbox organs.
- Minimum tendency to foam formation.

Specifications and Approval:

Exceeds requirements: **API GL-5/MT-1**

Typical properties:

LUBLAN LS 250

SAE Grade	250
Viscosity ASTM D-445	
cSt @ 40°C	665 – 680
cSt @ 100°C	38 – 42
Viscosity Index ASTM D-2270	≥95
Pour Point, °C, ASTM D-97	≤-6
Flash Point, °C, ASTM D-92	≥250
Density @ 15°C, Kg/l, ASTM D-1298	≥0,910

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

LS 250 Date Created: 18/01/2013 Last Edit: 17/05/2019

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofongone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it

P. IVA e C.F. 02682090648