



LUBLAN PCMO 0W-30

Fully synthetic engine oil

Product Description:

PCMO 0W-30 is a fully synthetic lubricant with advanced features designed to deliver outstanding engine protection and greater fuel savings. It allows you to extend the life and maintain the efficient emission installations for both diesel engines (DPF) for both those petrol (CAT).

Features:

PCMO 0W-30 is made with a mixture of synthetic bases and reinforced by balanced additive system.

Ensures:

- High engine protection against wear, even under extreme climatic conditions.
- Excellent characteristics at low temperatures for a protection of the motor in the starting phase.
- Low friction for fuel savings.
- It helps reduce particulate deposits in diesel particulate filters.
- It helps to reduce the poisoning of gasoline catalytic converters.

Specifications and Approval:

Exceeds requirements: **API SN/CF, ACEA C3, MB 229.51/229.52**

Typical properties:

LUBLAN PCMO 0W-30

SAE Grade	0W-30
Viscosity ASTM D-445	
cSt @ 40°C	61 – 68
cSt @ 100°C	11,6 – 12,4
Viscosity Index, ASTM D-2270	≥160
Flash Point, °C, ASTM D-92	≥220
Density @ 15°C, Kg/l, ASTM D-1298	≥0,850
Total Base Number, T.B.N., mgKOH/g, ASTM D-2896	7,9

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

PCMO 0W-30 Date Created: 18/01/2013 Last Edit: 17/05/2019

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofangone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it

P. IVA e C.F. 02682090648