



## **LUBLAN PCMO 10W-30**

*Semi-synthetic engine oils*

### **Product Description:**

**PCMO 10W-30** is an advanced semi-synthetic engine oil designed to keep engines running like new by providing exceptional cleaning power, wear protection and overall performance. **PCMO 10W-30** meets or exceeds the requirements of the latest industry standards required by modern gasoline engines.

### **Features and Benefits:**

- Helps prevent deposits and sludge build-up to enable long engine life
- Excellent overall lubrication and wear protection performance for many driving styles
- Outstanding performance during the maximum oil change interval recommended in a vehicle's owners manual

### **Specifications and Approval:**

Exceeds requirements: **API SN**

### **Typical properties:**

#### **LUBLAN PCMO 10W30**

SAE Grade	10W-30
Viscosity ASTM D-445	
cSt @ 40°C	59 – 64
cSt @ 100°C	9,2 – 10,5
Viscosity Index ASTM D-2270	≥145
Pour Point, °C, ASTM D-97	≤-29
Flash Point, °C, ASTM D-92	220
Density @ 15°C, Kg/l, ASTM D-1298	≥0,870
Colour	Light

### **Health and Safety:**

The data related to health, safety and environmental protection are provided in the material safety data sheets.

*The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.*

**PCMO 10W-30** Date Created: 18/01/2013 Last Edit: 17/05/2019

*This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.*

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofongone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: [info@gloil.it](mailto:info@gloil.it)

P. IVA e C.F. 02682090648