



LUBLAN PCMO 5W-20

Fully synthetic engine oil

Product Description:

PCMO 5W-20 is a 100% synthetic lubricant developed according to the specifications of the world's leading manufacturers to ensure the highest level of protection to high specific power engines of the last generation.

Is suitable for gasoline engines, naturally aspirated and turbocharged engines, and diesel engines and turbo diesel direct injection.

Features:

PCMO 5W-20 represents a great evolution in the field of high performance lubricants.

Thanks to the use of special modifiers of the coefficient of friction, allows the engine maximum power output and enhances the speed of response. It 'also able to resist the very strong thermal stresses typical of high power motors, so maintaining the highest level of cleanliness for extremely long periods.

PCMO 5W-20 allows:

- unconditional protection in extreme driving conditions
- Maximum power output and faster engine response
- Maximum cleanliness and efficiency of the engine over time
- Reduced fuel consumption
- Reduction of harmful emissions

Specifications and Approval:

Exceeds requirements: **API SN/CF, ACEA A1/B1**

Typical properties: *LUBLAN PCMO 5W-20*

| | |
|---|-------------|
| SAE Grade | 5W-20 |
| Viscosity ASTM D-445 | |
| cSt @ 40°C | 40,2 – 44,3 |
| cSt @ 100°C | 7,4 – 7,9 |
| Viscosity Index, ASTM D-2270 | ≥160 |
| Pour Point, °C, ASTM D-97 | ≤-30 |
| Flash Point, °C, ASTM D-92 | ≥210 |
| Density @ 15°C, Kg/l, ASTM D-1298 | ≥0,850 |
| Total Base Number, T.B.N., mgKOH/g, ASTM D-2896 | 8,1 |

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

PCMO 5W-20 Date Created: 18/01/2013 Last Edit: 17/05/2019

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.

GL OIL SPA - Industria Lubrificanti e Chimici - Loc. Boscofangone Zona ASI Nola-Marigliano - 80035 Nola (Na)

Tel. 081.826.9629 - Fax 081.826.9608 - <http://www.gloil.it> email: info@gloil.it

P. IVA e C.F. 02682090648