



LUBLAN PCMO 5W-30 C4

Fully synthetic engine oil

Product Description:

PCMO 5W-30 C4 is a 100% synthetic lubricant developed for Euro 4 & Euro 5 engines with long-drain oil refreshment periods, requiring the ACEA C4 quality. Especially suitable for Renault diesel passenger cars and vans with DPF exhaust system. Can be used for Nissan and Suzuki models where ACEA C4 is recommended.

Features:

PCMO 5W-30 C4 allows:

- Unconditional protection in extreme driving conditions
- Maximum power output and faster engine response
- Maximum cleanliness and efficiency of the engine over time
- Reduced fuel consumption
- Reduction of harmful emissions

Specifications and Approval:

Exceeds requirements: **ACEA C4, MB 226.51, Renault RN 0720, Nissan & Suzuki**

Typical properties: *LUBLAN PCMO 5W-30 C4*

SAE Grade	5W-30
Viscosity ASTM D-445	
cSt @ 40°C	69 – 73
cSt @ 100°C	11,5 – 12,1
Viscosity Index, ASTM D-2270	≥160
Pour Point, °C, ASTM D-97	≤-35
Flash Point, °C, ASTM D-92	≥210
Density @ 15°C, Kg/l, ASTM D-1298	≥0,850
Total Base Number, T.B.N., mgKOH/g, ASTM D-2896	7,9

Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.

PCMO 5W-30 C4 Date Created: 18/01/2013 Last Edit: 17/05/2019

This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.