



**LUBLAN Series HV**  
*HVI hydraulic fluids of superior quality*

**Product Description:**

mineral hydraulic oils of superior quality high viscosity index, containing anti-wear additives. By virtue of this additive they combine a high lubricating power with exceptional filterability. The careful selection of viscosity index improver additives allows a perfect maintenance of service levels.

Particularly suitable for hydraulic systems subjected to high loads and requiring both high anti-wear performance is excellent filterability, such as:

- external systems operating in the presence of strong variations in temperature (cold start and fully operating at high temperature).
- machinery operating indoor and equipped with control systems which require minimal changes in viscosity with temperature changes, such as machine tools for precision and playback machines.

The grades 32, 46 are particularly recommended as oils "multigrade" for lubrication of construction equipment and construction site employees throughout the year and particularly in variable climatic conditions. They are perfectly compatible with the seals commonly used in hydraulic systems, such as butyl-nitrile, fluorinated, polyurethane, polyester, perfluorinated. It exceeds the requirements defined by the main manufacturers of pumps and hydraulic motors, in accordance with the following specifications:

- DIN 51524/3 HVLP, ISO 11158 HV

Follow the manufacturers' recommendations with regard to the filtration and the oil change intervals. Before introducing HV, make sure your system is completely clean.

**Features and Benefits:**

- Wide operating temperature range.
- Easy cold start.
- Highest level of protection.
- Upper Filterability even in high humidity.
- Long operating life even under severe operating conditions.
- High-quality anti-wear, oxidation resistance and excellent thermal stability.

**Specifications and Approval:**

Exceeds requirements: **DIN 51524 Part 2 – Part 3 HVLP, ISO-L-HV**



## Typical properties:

## LUBLAN Series HV

| ISO Viscosity Grade                            | 32        | 46        | 68        | 100         |
|--|-----------|-----------|-----------|-------------|
| Viscosity ASTM D-445                           |           |           |           |             |
| cSt @ 40°C                                     | 29 - 34   | 42 - 48   | 63 - 70   | 90 - 105    |
| cSt @ 100°C                                    | 5,8 – 6,5 | 7,8 – 8,5 | 10 – 11,5 | 13,7 – 14,5 |
| Viscosity Index ASTM D-2270                    | ≥150      | ≥150      | ≥160      | ≥170        |
| Density @ 15°C, Kg/l, ASTM D-1298              | 0,860     | 0,865     | 0,865     | 0,885       |
| Pour Point, °C, ASTM D-97                      | -39       | -36       | -39       | -24         |
| Flash Point, °C, ASTM D-92                     | 200       | 204       | 208       | > 215       |
| Demulsibility, min, ASTM D-1401                | 5         | 5         | 10        | 10          |
| Anticorrosive (B), ASTM D-665                  | passa     | -         | -         | -           |
| Copper Strip Corrosion (3h a 100°C) ASTM D-130 | 1b        | 1b        | 1b        | 1b          |
| Number of neutralization, mgKOH/g, ASTM D-974  | 0,22      | 0,22      | 0,22      | 0,22        |

## Health and Safety:

The data related to health, safety and environmental protection are provided in the material safety data sheets.

*The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.*

Series HV Date Created: 18/01/2013 Last Edit: 24/05/2019

*This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.*