



## **LUBLAN SEO 4T 5W40**

*Lubricant for 4-stroke motorcycles*

### **Product Description:**

SEO 4T 5W-40 is a multigrade lubricant formulated with synthetic base oils with a high refining and detergent additives and inhibitors for engines of motorcycles and maxi scooters 4 times.

### **Features and Benefits:**

- It allows to obtain an excellent engine cleanliness and effective protection against wear, corrosion and rust.
- The particular gradation allows to obtain good performance even at high temperatures.

### **Specifications and Approval:**

Exceeds requirements: **API SN, JASO MA/MA2**

### **Typical properties:**

### **LUBLAN SEO 4T 5W40**

SAE Grade	5W40
Viscosity ASTM D-445	
cSt @ 100°C	13,6 – 14,2
Viscosity Index ASTM D-2270	≥160
Pour Point, °C, ASTM D-97	≤-39
Flash Point, °C, ASTM D-92	≥220
Density @ 15°C, Kg/l, ASTM D-1298	≥0,855

### **Health and Safety:**

The data related to health, safety and environmental protection are provided in the material safety data sheets.

*The above figures are those relating to normal manufacturing tolerances and do not constitute a specification.*

SEO 4T 5W40 Date Created: 18/01/2013 Last Edit: 20/07/2018

*This data sheet and the information it contains is believed to be correct with specific reference to the date of printing. The accuracy or completeness of the data and information contained in this publication are not binding in any way the responsibility of the company. The user has the obligation to evaluate and use products safely and in accordance with all applicable laws and regulations currently in force. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a license. The GL OIL S.P.A. can not be held responsible for any damage or injury resulting from incorrect use of the product or of any lessening the recommendations or any risk arising from the nature of the material.*